取扱説明書

Defi-Link Meter ADVANCE C2 DF12601 ～ DF13402
デフィーリンクメーターアドバンスシーツー

Defi-Link Meter ADVANCE RS DF13501 ～ DF14101
デフィーリンクメーターアドバンスアールエス

'13.06-1

SI Series

本製品は Defi-Link ADVANCE Control unit（アドバンスコントロールユニット）と一緒に使用する製品です。本製品だけでは動作しません。本製品をご使用の際は必ずアドバンスコントロールユニットの取扱説明書も合わせてお読みください。
また、ラインナップ以外の項目（安全に関するご注意、寸法、仕様、取付方法等）については ADVANCE CR/ADVANCE BF の取扱説明書をご参照ください。

ラインナップ (お客様へ)

		ADVANCE C2			ADVANCE RS	
機種名	表示範囲	ブルーモデル	ピンクモデル	サイズ		サイズ
ターボ計 2.0	-100 ～ +200kPa	DF12601	DF12602		DF13501	
インマニ計	-100 ～ +20kPa	DF12701	DF12702		DF13601	
油圧計	0 ～ 1000kPa	DF12801	DF12802		DF13701	
燃圧計	0 ～ 600kPa	DF12901	DF12902	Φ60	DF13801	Φ52
油温計	50 ～ 150℃	DF13001	DF13002		DF13901	
水温計	20 ～ 120℃	DF13101	DF13102		DF14001	
排気温度計	200 ～ 1100℃	DF13201	DF13202		DF14101	
タコメーター	0 ～ 9000rpm	DF13301	DF13302	Φ80		
タコメーター	0 ～ 11000rpm	DF13401	DF13402			

製品仕様：照明色 (お客様へ)

■ADVANCE C2

指針：白
文字板：黒
文字・数字・目盛り（照明オン時）：白
文字板リング（照明オン / オフ時）：ブルー / ピンク

※照明色の切り替えはできません。
※使用方法に関しては ADVANCE BF と同じです。

■ADVANCE RS

指針：照明オフ時→白 / 照明オン時→赤
文字板：黒
文字・数字・目盛り（照明オフ時）：白
照明色：緑色と電球色の 2 色間で切替可能

※使用方法に関しては ADVANCE CR と同じです。

デフィーリンクメーター アドバンス C2・アドバンス RS 取扱説明書
■発行　初版 2013 年 06 月
■製造元　日本精機株式会社
■連絡先　日本精機株式会社 Defi お客様相談室
【住所】〒940-2141 新潟県長岡市藤橋 1-190-1 R&D センター Defi
【電話番号】(03) 3835-3639 (Japanese only)
【FAX 番号】(03) 3834-8116
【受付時間】10:00 ～ 12:00, 13:00 ～ 17:00（土・日曜、祭日、当社休日を除く平日）
【Web サイト】http：//www.nippon-seiki.co.jp/defi/
PAT. 3019067　PAT. 3019939

日本精機株式会社

Manual

Defi-Link Meter ADVANCE C2 DF12601 ～ DF13402
Defi-Link Meter ADVANCE C2

Defi-Link Meter ADVANCE RS DF13501 ～ DF14101
Defi-Link Meter ADVANCE RS

SI Series

This product functions with Defi-Link ADVANCE Control unit. This product alone does not function. Please refer to Defi-Link ADVANCE Control unit operation manual as well.
In addition, please refer to ADVANCE CR/ADVANCE BF manual for contents such as safety warning, specifications, dimensions, how to install, etc.

Lineup (for customer)

		ADVANCE C2			ADVANCE RS	
Product name	Display range	Blue Model	Pink Model	Size		Size
Turbo2.0	-100 ～ +200kPa	DF12601	DF12602		DF13501	
In-Mani Press	-100 ～ +20kPa	DF12701	DF12702		DF13601	
Oil Press	0 ～ 1000kPa	DF12801	DF12802		DF13701	
Fuel Press	0 ～ 600kPa	DF12901	DF12902	Φ60	DF13801	Φ52
Oil Temp	50 ～ 150℃	DF13001	DF13002		DF13901	
Water Temp	20 ～ 120℃	DF13101	DF13102		DF14001	
Exhaust Temp	200 ～ 1100℃	DF13201	DF13202		DF14101	
Tachometer	0 ～ 9000rpm	DF13301	DF13302	Φ80		
Tachometer	0 ～ 11000rpm	DF13401	DF13402			

Specifications：Illumination color (for customer)

■ADVANCE C2

Gauge pointer：white
Gauge dial color：black
Characters, scale (ILM ON)：white
Gauge dial ring color (ILM ON/OFF)：blue/pink

※The ring color cannot be changed.
※"How to operate" is the same as that of ADVANCE BF.

■ADVANCE RS

Gauge pointer：ILM OFF→white / ILM ON→red
Gauge dial color：black
Characters, scale (ILM OFF)：white
Illumination color：switchable between green and warm white

※"How to operate" is the same as that of ADVANCE CR.

Defi-Link Meter ADVANCE C2 & ADVANCE RS Operation Manual
■ Issue　First edition: June, 2013
■ Manufacturer　Nippon Seiki Co., Ltd.
■ Contact Information　Defi, Nippon Seiki Co., Ltd.
[Address] 190-1 Fujihashi 1-chome, Nagaoka-shi, Niigata 940-2141 JAPAN
[URL] http://www.defi-shop.com/
PAT. 3019067　PAT. 3019939

NIPPON SEIKI CO.,LTD.